

19



Europäisches Patentamt

European Patent Office

Office européen des brevets

11

Publication number:

0 204 542

A3

12

EUROPEAN PATENT APPLICATION

21 Application number: 86304204.0

51 Int. Cl.: G 06 K 7/08


22 Date of filing: 03.06.86

30 Priority: 05.06.85 GB 8514219

43 Date of publication of application: 10.12.86
Bulletin 86/5084 Designated Contracting States: AT BE CH DE FR GB IT LI
LU NL SE88 Date of deferred publication of search
report: 06.05.87 Bulletin 87/1971 Applicant: Bertenshaw, Philip Hall, 18 Lower Fold,
Marple Bridge Cheshire (GB)
Applicant: Jones, John, 82 Guywood Lane Romiley,
Stockport Greater Manchester (GB)72 Inventor: Bertenshaw, Philip Hall, 18 Lower Fold, Marple
Bridge Cheshire (GB)
Inventor: Jones, John, 82 Guywood Lane Romiley,
Stockport Greater Manchester (GB)74 Representative: Quest, Barry et al, M'CAW &
CO. 41-51 Royal Exchange Cross Street, Manchester
M2 7BD (GB)

54 Identification system.

57 An identification system comprises reading equipment (1) and an identification device (2) which can be inductively coupled via respective coils (L1, L2). The identification device (2) does not contain an internal battery but is energised by the reading equipment via the coupled coils (L1, L2). A control element such as a load resistor (R1) is provided in the identification device (2) and acts to modify the coupling of the coils (L1, L2) in a manner which can be interpreted by a reading circuit (8) in the reading equipment (1). The load resistor (R1) may be switched off and on by a transistor (TR) in a manner determined by coded digital signals derived from a data store (6).



EP 0 204 542 A3

Best Available Copy



European Patent
Office

EUROPEAN SEARCH REPORT

0204542

Application number

EP 86 30 4204

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
X	US-A-4 517 563 (DIAMANT) * Figure 1; column 2, line 16 - column 3, line 11 *	1,3-10	G 06 K 7/08
X	--- AU-A- 515 616 (NEDERLANDSCHE APPARATENFABRIEK NEDAP) * Figures 1,2; claim 1; page 4, line 3 - page 7, line 9; page 8, line 15 - page 9, line 17 *	1-4,6-10	
X	--- DE-A-3 242 551 (GÖTTING) * Figures 1,2; page 21, line 11 - page 22, line 23 *	1,3-8,10	
P,X	--- US-A-4 546 241 (WALTON) * Figure 1; column 2, line 8 - column 5, line 62 * -----	1-10	TECHNICAL FIELDS SEARCHED (Int. Cl. 4) G 06 K G 07 C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 06-02-1987	Examiner GYSEN L.A.D.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 204 542
A2

(12)

EUROPEAN PATENT APPLICATION

(71) Application number: 86304204.0

(51) Int. Cl.: G 06 K 7/08

(72) Date of filing: 03.06.86

(30) Priority: 05.06.85 GB 8514219

(43) Date of publication of application:
10.12.86 Bulletin 86/50

(84) Designated Contracting States:
AT BE CH DE FR GB IT LI LU NL SE

(71) Applicant: Bertenshaw, Philip Hall
18 Lower Fold
Marple Bridge Cheshire(GB)

(71) Applicant: Jones, John
82 Guywood Lane Romiley
Stockport Greater Manchester(GB)


(72) Inventor: Bertenshaw, Philip Hall
18 Lower Fold
Marple Bridge Cheshire(GB)

(72) Inventor: Jones, John
82 Guywood Lane Romiley
Stockport Greater Manchester(GB)

(74) Representative: Quest, Barry et al,
M'CAW & CO. 41-51 Royal Exchange Cross Street
Manchester M2 7BD(GB)

(54) Identification system.

(57) An identification system comprises reading equipment (1) and an identification device (2) which can be inductively coupled via respective coils (L1, L2). The identification device (2) does not contain an internal battery but is energised by the reading equipment via the coupled coils (L1, L2). A control element such as a load resistor (R1) is provided in the identification device (2) and acts to modify the coupling of the coils (L1, L2) in a manner which can be interpreted by a reading circuit (8) in the reading equipment (1). The load resistor (R1) may be switched off and on by a transistor (TR) in a manner determined by coded digital signals derived from a data store element (6).



Craydon Printing Company Ltd

0204542

(M15274A)
(28.2.85)

- 1 -

IDENTIFICATION SYSTEM

This invention relates to an identification system of the kind comprising a personal identification device, such as an identification card, which can be verified by automatic reading equipment for example
5. to provide access to security premises or for other purposes.

Identification cards are known which have identifying data which can be read with a magnetic reader. There are also cards which have data which can be read with a bar-code reader. In each case there is the problem that the reading equipment operates with a wiping or scanning
10. action utilising a small gap between the card and reader whereby the problem arises that identification of data can be readily disturbed by vandalism of the equipment or accumulation of dirt on the card or within the equipment. Infra-red reading equipment similarly is subject to disturbances in so far as it is necessary to insert an identification
15. card into an aperture in which the card is maintained accurately in predetermined disposition relative to the reader.

Transponder proximity card reading systems are less prone to disturbance and give good hand-free operation, but these can be inconvenient and expensive in so far as a battery power supply is
20. provided within the identification card and sophisticated control circuitry is required to ensure adequate battery life. There are proximity reading systems which do not require a battery power source but these rely on the use of complex and expensive reading equipment.

An object of the present invention is to provide a simple, convenient
25. and inexpensive identification system which is reliable in operation and utilises an identification device which need not be provided with an internal battery power source.